



PCT/IB 04 / 02288
(12.07.04)



INVESTOR IN PEOPLE

REC'D 12 JUL 2004	
WIPO	PCT

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.


In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

**PRIORITY
DOCUMENT**
SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)

Signed 

Dated 5 May 2004



BEST AVAILABLE COPY

The
Patent
Office

THE PATENT OFFICE

17 JUL 2003

NEWPORT

1/77

Request for grant of a patent

(See notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office
Cardiff Road
Newport
Gwent NP10 8QQ

Your reference

PHGB 030115GBP

Patent application number

(The Patent Office will fill in this part)

0316692.3

17JUL03 E823206-2 D02879

P01/7700 0.00-0316692.3

Full name, address and postcode of the or of each applicant (underline all surnames)

KONINKLIJKE PHILIPS ELECTRONICS N.V.
GROENEWOUDSEWEG 1
5621 BA EINDHOVEN
THE NETHERLANDS
07419294001

Patents ADP Number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

THE NETHERLANDS

Title of the invention

ENHANCED MULTI-PATH FOR MIMO DEVICES

Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Philips Intellectual Property and Standards
Cross Oak Lane
Redhill
Surrey
RH1 5HA
08359655001

Patents ADP number (if you know it)

If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority Application number
(if you know it)

Date of filing
(day/month/year)

If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing
(day/month/year)

Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer "Yes" if:

YES

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d)).

Patents Form 1/77

Enter the number of sheets for any of the following items you are filing with this form.
Do not count copies of the same document.

Continuation sheets of this form

Description	10
Claims(s)	4
Abstract	1
Drawings	4

3. If you are also filing any of the following, state how many against each item:


Priority Documents

Translations of priority documents
Statement of inventorship and right
to grant of a patent (*Patents Form 7/77*)
Request for preliminary examination and
search (*Patents Form 9/77*)
Request for substantive examination
(*Patents Form 10/77*)
Any other documents
(Please specify)

1.

I/We request the grant of a patent on the basis of this application.

Signature



Date 16/7/2003

2. Name and daytime telephone number of person to contact in the United Kingdom

01293 815438

(A. G. WHITE)

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered "Yes" Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office

DESCRIPTION

ENHANCED MULTI-PATH FOR MIMO DEVICES

The present invention relates to wireless networks, and in particular to methods and apparatus for enhancing the efficiency of communication
5 between a transmitter and a receiver on a wireless network.

The use of wireless networks in the office and the home for communication between multiple devices has recently proliferated. Such networks are typically characterised by the existence of multiple possible
10 communication paths or channels between devices, in which each path may be susceptible to variable propagation efficiency, particularly as devices move around within the network, or as obstacles to transmission move around between antennae of the various devices or as RF energy scattering objects move around within the network area.

15 In a typical transmission network, a transmitter transmits data packets to a receiver device which acknowledges correct receipt of the packet with an acknowledge (ACK) signal. If the data received by the receiver contain errors or only part of the transmission is received, the receiver responds with a no-acknowledge (NACK) signal. There are
20 various protocols for handling situations where the receiver receives no part of the packet at all. For example, in the event the transmitter receives no type of acknowledgement within a predetermined period of time, it assumes total failure of transmission and retries transmission at a later time.

25 The availability of multiple transmission paths in a network has previously been exploited to increase the reliability of transmission of data packets between devices. The multiple transmission paths in a multiple-input-multiple-output (MIMO) device environment can be provided by way of plural antennae on each device, and/or by several different transceiver
30 nodes and transmission pathways between the transmitter and receiver.

US 2003/0012318 describes a system in which data to be transmitted from a transmitter to a receiver is divided into blocks, each of which is transmitted on a separate antenna. The receiver checks whether all blocks have been received and then issues an acknowledgement. If the transmission fails, the blocks are retransmitted using different spatial and temporal diversity for combination with the previously received blocks to obtain a better signal to noise ratio.

Similarly, EP 1294120 A1 describes a multiple-input-multiple-output device transmission system in which a transmitter transmits data to a receiver using plural antennae according to first predetermined transmission conditions defining the encoding, interleaving, modulation and sub-stream splitting transformations to be applied. The receiver returns either an acknowledge (ACK) or a no-acknowledge (NACK) signal. In the event of a NACK signal being returned, the transmitter retransmits the data according to second predetermined transmission conditions, the choice of second transmission conditions being so as to attempt to reduce the transmission error probability.

Both of these techniques generally attempt to alleviate transmission problems by varying the way in which the data is distributed across the same multiple paths between the transmitter and receiver in the event that a transmission failure occurs.

Another problem in communication between transmitter and receiver is the data transmission overhead that is implied by the repeated use of ACK and NACK requests (the signalling overhead), and the need for retransmission of data (the retransmission overhead).

One approach to alleviating this problem is described in US 2003/0067890. In this system, a transceiver receives standard protocol data units for transmission to receiver units within the wireless network. The transceiver divides the standard protocol data units into smaller sub-protocol units that are more suited to transmission over the wireless network, and provides the receiver with a map of the sub-protocol units to be expected. The sub-protocol units may be transmitted to the receiver on

different frequency channels and time slots. The transmitter includes an acknowledge request indicator in the transmission to the receiver with only a subset of the sub-protocol units, so that the receiver need only acknowledge groups of the sub-protocol units. Using the map, the receiver can acknowledge which of the sub-protocol units of a group have been received, and the transceiver need only retransmit those particular sub-protocol units that were not received by the receiver. Thus, an acknowledge request need not be provided for every transmitted sub-protocol unit and the amount of data to be retransmitted is reduced.

A problem that exists with all of these prior art methods is that it remains incumbent upon the originating transmitter to monitor acknowledge messages and to repeat data transmission to some extent in the event of a transmission failure. A further problem exists in that although the distribution of the data for retransmission across the various paths of the network may be altered after failure, the actual path configuration used to transmit that data remains effectively the same.

It is an object of at least one aspect of the present invention to provide a method and apparatus for improving the results obtained during retransmission of data after a transmission failure.

It is an object of at least one aspect of the present invention to reduce the burden on the transmitting device in respect of supervising the acknowledgement messages and data retransmission. Accordingly, it is an object of at least one aspect of the invention to reduce the signalling overhead and the retransmission overhead on the transmitting device.

The invention is particularly relevant and useful (though not exclusively so) where a transmitting device may be a portable, low power device with limited battery capacity which uses a network including repeater devices which are not power constrained.

For example, the network may comprise a plurality of devices that are mains powered (eg. wireless LAN repeater stations, desktop personal computers, printers, scanners, fax machines etc) and a plurality of portable

devices that are not mains powered (eg. notebook computers, mobile telephones, PDAs etc).

According to one aspect, the present invention provides a method
5 of transmitting data between a transmitter and a receiver, comprising the steps of:

transmitting, by the transmitter, a data packet onto multiple paths of a network between the transmitter and the receiver, at least one of the paths including at least one repeater transceiver node;

10 issuing a NACK signal over the network, by the receiver, in the event that the data packet is not properly received; and

retransmitting the data packet onto the network by at least one of the repeater nodes upon receipt of the NACK signal.

15 According to another aspect, the present invention provides a repeater node for forwarding data packets, received from a transmitter node, to a receiver node that is the end destination of the packet, in a network, comprising:

a receive module for receiving data packets originating from the
20 transmitter;

a transmit module for forwarding the data packet to another node in the network;

a pending packet buffer for storing forwarded data packets; and

25 retransmission means for retransmitting over the network previously forwarded data packets for which NACK signals are received.

For the avoidance of doubt, the expression 'transmitter' is used to define the originator of a data packet transmitted onto the network, and the expression 'receiver' is used to define the intended addressee or ultimate
30 destination of the data packet. These terms are distinct from 'intermediate repeater nodes', or 'transceivers' which terms describe devices that merely serve to forward data packets through the network. However, it will be

understood that, in general, a node that is capable of acting as a transmitter and/or a receiver for originating and/or terminating a data packet may also act as a repeater node for other (different) data packets that originate from and terminate at other nodes.

5 It is also noted that the expression 'retransmitting' is used to define the action of retransmitting a data packet for which a NACK signal has been issued, ie. the action of originating a retransmission of the packet. This is distinct from merely forwarding an existing data packet (including a retransmitted data packet) which is already in transit.

10 Figure 1 shows a schematic diagram of a wireless network comprising a transmitter, a receiver and at least two transceiver nodes, illustrating transmission paths for a data packet from the transmitter to the receiver;

15 Figure 2 shows a schematic diagram of the wireless network of figure 1 illustrating transmission paths for return of a NACK signal from the receiver to the transmitter;

Figure 3 shows a schematic diagram of the wireless network of figure 1 illustrating paths for retransmission of the data packet by the transceiver nodes and, optionally by the transmitter; and

20 Figure 4 shows a schematic diagram of a repeater suitable for implementing the present invention.

With reference to figure 1, a network 5 includes a number of nodes. 25 A first node is a transmitter 10 which is provided with two transmit antennae 11, 12. These may be omnidirectional or directional, and may point in different directions or overlapping directions in accordance with conventional device design. A second node is a receiver 20 which is also provided with two receive antennae 21, 22 in similar fashion. Also 30 provided within the network 5 is a first repeater transceiver device 30 with transmit and receive antennae 31, 32. A second repeater transceiver device 40 has transmit and receive antennae 41, 42.

Although not shown for simplicity of illustration, it will be understood that the transmitter 10 could also act as a receiver or a repeater transceiver; receiver 20 could also act as a transmitter or a repeater transceiver; and repeater transceivers 30, 40 could also act as transmitters and receivers in their own right. Furthermore, any of the antennae could be multiplexed to act as both transmit and receive antennae according to known practices.

Preferably, each of the nodes 10, 20, 30, 40 in the network 5 has one or more transmission paths between itself and adjacent or nearby nodes. For example, as shown in figure 1, the transmitter node 10 is configured for first and second direct transmission paths 13, 14 from antennae 11, 12 respectively to antenna 31 of repeater 30. Similarly, transmitter node 10 is configured for third and fourth direct transmission paths 15, 16 from antennae 11, 12 respectively to antenna 41 of repeater 40. Each of these repeater transceivers 30, 40 is respectively configured for a direct transmission path 33, 43 from antennae 32, 42 to the receiver 20. Data packets from transmitter 10 can thereby be forwarded to receiver 20.

In the illustration, transmitter 10 is also configured such that at least one direct transmission path 17 exists between itself and the receiver 20, eg. between antenna 12 and antenna 21, and an indirect transmission path 18 exists between itself and the receiver 20. The indirect path is formed by reflection, refraction or scattering of the signal off some object 50.

In the event of transmission of a data packet originating from the transmitter 10, the data packet reaches the receiver by at least one of the various paths illustrated, both direct and indirect, and also by way of repeater transceivers 30, 40.

In the event that the receiver 20 receives the data packet in full, ie. the data is complete and uncorrupted, the receiver issues an ACK signal which is returned to the transmitter and/or repeater transceivers over similar paths as those described in connection with figure 1. Referring

now to figure 2, in the event that the data does not arrive at the receiver 20 complete and uncorrupted, the receiver returns a NACK signal. The NACK signal is transmitted over various possible paths 23 – 26 as shown. For example, path 23 may be directed to antenna 32 of transceiver repeater 30; path 25 may be directed to antenna 11 of transmitter 10; path 24 may be directed at antenna 41 of repeater 40 and path 26 may be directed at antenna 42 of repeater 40.

In the prior art techniques, the transmitter 10 will await receipt of either the ACK or the NACK signal, either over a direct path, an indirect path, or via a repeater, before determining what further action to take. In the event that an ACK signal is received, the transmitter 10 knows that it can purge the data packet from its pending queue and, if necessary, report successful completion to a host device (not shown). In the event that a NACK signal is received, in prior art techniques the transmitter 10 knows that it must retransmit the data packet.

If the transmitter simply retransmits the data packet, there is a strong likelihood that whatever phenomena obstructed the first transmission of the data packet on the several available paths may still prevail, and the retransmitted data packet will then also result in a returned NACK signal. Even if, as proposed in some of the prior art, the transmitter adjusts the power of one or more of the antennae, or adjusts the data distribution of the data packet across the various paths (in the event that data packet splitting techniques for spatial and temporal diversity are employed), there is still a prospect that the same interference conditions will still prevail and again result in a returned NACK signal.

The present invention proposes that the receiver nodes 30, 40 can also or instead be used to initiate (ie. originate) retransmission of the data packet upon receiving a NACK signal. Thus, the NACK signal issued by the receiver 20 on path 23 will be received by the repeater 30 and the NACK signal issued by receiver on path 26 will be received by the repeater 40.

One or both repeaters 30, 40 may be programmed to become active retransmitters in the event of a received NACK signal in respect of a data packet for which they previously accepted forwarding responsibility. (They may also act in their conventional roles as forwarding or repeater nodes to return the NACK signal to the transmitter 10.)

With reference to figure 3, it will be seen that in this instance, for the purposes of retransmission of the data packet, the pathways to the receiver 20 are increased, because all antennae and or transmission pathways from the repeater nodes, direct and indirect, can be used to retransmit the data packet.

The repeaters 30, 40 may also forward the NACK signal on to the transmitter 10 that originated the data packet, in which case this too may respond with a retransmission of the data packet, thus further increasing the probability that the retransmitted data packet will reach the destination receiver.

It will be understood from the foregoing that the transmitter does not need to partake in the retransmission of the data packet if that responsibility is devolved to one or more repeaters. In this case, the transmitter need not even listen for NACK signals in respect of data packets that it has sent. This is a particularly useful feature for low power devices or generally devices with a restricted power source, such as battery powered devices.

Figure 4 shows a preferred embodiment of repeater transceiver node 30. The repeater node 30 includes antennae 31, 32, each with its own transmit / receive driver circuit 61, 62. Preferably each repeater 30 in the network is adapted to receive data packets from at least one circuit 61, 62 and to place it into a FIFO packet queue 60 from which the data packets are forwarded under the control of control circuit 65.

Upon forwarding data packets, they are also transferred into a pending buffer 63 where they wait pending a responsive ACK or a NACK signal. Then, if a NACK signal is received in respect of a previously forwarded data packet, the repeater node 30 acts as an originating

transmitter to retransmit the data packet stored in the pending buffer 63 to the receiver 20. Conversely, in the event that an ACK signal is received, the repeater clears the respective data packet from the pending buffer 63.

Each data packet in the pending buffer 63 preferably includes a
5 time stamp which is used to trigger a retransmission after a predetermined retransmission delay in the event that neither ACK nor NACK signals are received.

It will be understood that a NACK signal issued by the receiver 20 may be responded to by a number of repeaters 30, 40 and also possibly
10 by the transmitter 10. This increases the probability that at least one copy of the retransmitted data packet will arrive at the receiver.

A number of possible protocols may be deployed for ensuring appropriate data packet management. Each transmitted data packet is preferably uniquely identified so that each node can determine whether it
15 is a data packet for which it has retransmission responsibility and to relate it to respective ACK / NACK signals. Depending upon network and data transport requirements, repeaters that fail to receive either an ACK or a NACK signal after a predetermined time may be programmed to either discard the data packet, or to retransmit the data packet.

20 Originating transmitters may be programmed to either require an ACK signal or not. In the event that the data transport protocols require that the transmitter get acknowledgement of correct receipt of data packets by the receiver, this can be done in a number of ways. For example, repeaters 30, 40 may be programmed to forward only ACK signals (but not
25 NACK signals) to the transmitter, thus ensuring that all retransmission overhead falls on the repeaters.

This latter feature may be sufficient where the communication between transmitter and at least one repeater is highly reliable. However, where the transfer of data packet from transmitter to repeater is not
30 guaranteed, the transmitter may be programmed with a retransmittal delay (the interval between the first transmittal of a packet and an attempted retransmittal in the event of no ACK or NACK signal being received) which

is substantially greater than the retransmittal delay of the repeaters. In this arrangement, the repeaters 30, 40 will make several attempts to complete successful data packet transfer before the transmitter 10 does so. This clearly has beneficial implications for the power demand of the transmitter 10 compared with the repeaters.

In another arrangement, particularly useful where the transmitter is a power constrained device, the transmitter could be arranged not to listen for ACK or NACK signals at all. Repeater nodes may be programmed to temporarily store plural ACK signals from a series of data packets and transfer them in a burst to the transmitter at predetermined intervals or on demand by the transmitter.

Numerous alternative arrangements of repeater may be envisaged. For example, the packet queue 60 is not strictly necessary if real time forwarding is deployed. The packet queue 60 and the pending buffer 63 could be combined simply by flagging the status of respective entries.

Other embodiments are intentionally within the scope of the appended claims.

CLAIMS

1. A method of transmitting data between a transmitter (10) and a receiver (20), comprising the steps of:

transmitting, by the transmitter, a data packet onto multiple paths
5 (13 – 18) of a network (5) between the transmitter and the receiver, at
least one of the paths including at least one repeater transceiver node (30,
40);

issuing a NACK signal over the network, by the receiver (20), in the
event that the data packet is not properly received; and

10 retransmitting the data packet onto the network by at least one of
the repeater nodes (30, 40) upon receipt of the NACK signal.

2. The method of claim 1 in which the retransmitting step is effected by
all repeater nodes that forwarded the data packet and that receive the
15 NACK signal.

3. The method of claim 1 in which the retransmitting step is effected by
at least one of the repeater nodes (30, 40) and the transmitter (10).

20 4. The method of claim 1 in which the transmitter (10) does not
retransmit the original data packet in the event of the issuing of a NACK
signal by the receiver.

5. The method of claim 4 in which the transmitter (10) does not listen
25 for NACK signals relating to its own transmitted data packets.

6. The method of claim 1 in which the step of retransmitting the data
packets onto the network (5) by the at least one repeater node (30, 40)
includes the step of using multiple paths available from the repeater node
30 to the receiver.

7. The method of claim 1 further including the step of the receiver (20) issuing an ACK signal in the event that the data packet is correctly received, the at least one repeater node (30, 40) forwarding the ACK signal to the transmitter (10).

8. The method of claim 1 further including the step of retransmitting the data packet, by the repeater node (30, 40), after a first predetermined retransmittal interval if no ACK or NACK signal is received in respect of a forwarded data packet.

9. The method of claim 8 further including the transmitter (10) retransmitting the data packet step after a second predetermined retransmittal interval if no ACK signal is received, the second predetermined retransmittal interval being greater than the first predetermined retransmittal interval.

10. A repeater node (30; 40) for forwarding data packets, received from a transmitter node (10), to a receiver node (20) that is the end destination of the packet, in a network (5), comprising:

a receive module (61) for receiving data packets originating from the transmitter;

a transmit module (62) for forwarding the data packet to another node in the network;

a pending packet buffer for storing forwarded data packets; and

retransmission means for retransmitting over the network previously forwarded data packets for which NACK signals are received.

11. The repeater node of claim 10 further including purge means for removing a stored data packet from the pending packet buffer when an ACK signal received in respect of that data packet.

12. The repeater node of claim 10 in which the retransmission means includes means for retransmitting the data packet over all available paths.

13. The repeater node of claim 10 adapted to forward ACK signals to the transmitter but not to forward NACK signals to the transmitter.

14. The repeater node of claim 10 in which the retransmission means further includes means for retransmitting the data packet after a first predetermined retransmittal interval when no corresponding ACK or NACK signal is received.

15. A network of communicating nodes including a transmitter (10), a receiver (20) and at least one repeater (30, 40) for forwarding data packets, received from a transmitter node (10), to the receiver node (20) that is the end destination of the packet, comprising:

a receive module (61) in the repeater node for receiving data packets originating from the transmitter;

a transmit module (62) in the repeater node for forwarding the data packet to another node in the network;

a pending packet buffer (63) in the repeater node for storing forwarded data packets; and

retransmission means in the repeater node (30, 40) for retransmitting, over the network (5), previously forwarded data packets for which NACK signals are received.

16. The network of claim 15 in which the retransmission means, in the repeater node (30, 40), further includes means for retransmitting the data packet after a first predetermined retransmittal interval when no corresponding ACK or NACK signal is received.

17. The network of claim 16 further including second retransmission means, in the transmitter (10), for retransmitting the data packet after a

second predetermined retransmittal interval longer than the first retransmittal interval, when no corresponding ACK or NACK signal is received.

5 18. Apparatus substantially as described herein with reference to the accompanying drawings.

19. A method substantially as described herein with reference to the accompanying drawings.

10

ABSTRACT

ENHANCED MULTI-PATH FOR MIMO DEVICES

A protocol for forwarding data packets over a network. An originating transmitter sends a data packet over the network to a destination receiver. The packet is forwarded by one or more repeaters within the network. The repeaters assume responsibility for originating re-transmissions of the packet if the packet is not correctly received by the destination receiver (eg. if a NACK signal is returned from the receiver or if no type of acknowledgement signal is returned from the receiver). Re-transmission of the packet by multiple repeaters effectively modifies the data paths by which the data packet travels to the receiver increasing probability that the packet gets through to the receiver. The transmitter may be configured not to respond to any NACK signals for packets it has sent, thereby transferring retransmission overhead and signalling overhead to the repeaters. This is of particular utility in networks where the originating transmitter is a battery-powered device and the repeaters are not power limited.

[Figure 3]

1/4

Time 1: Initial transmission




FIG. 1

2/4

Time 2: ACK/NACK by Rx




FIG. 2

3/4

Time 3: Repeat transmission




FIG. 3

PHGBO3011SGBP

4/4





Fig. 4



PCT/IB2004/002288



**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☒ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☒ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.